

# ACRYLIC SEALER

## INTRODUCTION

Jesmonite® Acrylic Sealer is a pure acrylic coating compatible with AC100, 200 & 300. It's a durable, flexible product designed for use in a variety of applications. The new formulation is designed to ensure the matte appearance of Jesmonite is maintained whilst also being easily applied using brush, roller, or spray.

Acrylic Sealer has always been a firm favourite in the arts, crafts and creative sectors and is heralded as an easy to use, yet extremely high-performing and compatible product. Due to popular demand, we are happy to announce it's return in an improved newly formulated format.

Products sealed with Acrylic Sealer will require re-coating at 6-to-10-year intervals, to ensure optimal results. Please be aware that when used in conjunction with AC200 and AC300 you will not receive the same level of protection when used externally.

Project specific advice can be obtained by emailing our technical department on [support@jesmonite.co.uk](mailto:support@jesmonite.co.uk).

## ACRYLIC SEALER APPLICATION

We recommend for best results that two coats of Acrylic Sealer should be applied onto low porosity surfaces such as AC100, with the first coat being diluted with 10 – 20% water. Diluting the first coat will aid the chemical bonding process of the Acrylic Sealer.

The second proprietary coat is applied once the initial diluted coat is touch dry. Do not allow the first coat to dry completely before applying the second coat. In principle the application of several thin coats is preferable to one thick coat.

Remember that Acrylic Sealer goes a long way, therefore small quantities can cover large areas – do not over apply the product and ensure you work with small doses to control the process.

Acrylic Sealer can also be diluted with water and pigmented using the Jesmonite Liquid Pigments to create colour washes to add a patina or to artificially age casts.

## KEY BENEFITS

- Increased Water Resistance
- Easy To Use
- Cost Effective
- Cross Product Compatibility



Jesmonite® is a Registered Trademark

The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended.

**Contact details**  
Jesmonite Limited  
Challenge Court

Bishops Castle  
Shropshire SY9 5DW  
United Kingdom

Tel. +44 (0)1588 630302  
Fax. +44 (0)1588 630304  
[www.jesmonite.co.uk](http://www.jesmonite.co.uk)