Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 05.06.2019

Version number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: RockCast-150 ISOCYANATE (B)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Polyurethane resin
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: SIKA AUTOMOTIVE FRANCE SAS
 15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE Tél.+33 (0)1 34 40 34 60
- Further information obtainable from: DPT HSE +33 (0)1 34 40 34 60 safety@fr.sika.com
- *1.4 Emergency telephone number: ORFILA* : +33 (0)1 45 42 59 59 +44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling: 4,4'-Methylenediphenyl diisocyanate, oligomers
Hazard statements H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31



(Contd. of page 1)

Printing date 05.06.2019

Version number 3

Trade name: RockCast-150 ISOCYANATE (B)

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

· 2.3 Other hazards

· Results of PBT and vPvB assessment Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

0 1		
	4,4'-Methylenediphenyl diisocyanate, oligomers	50-100%
Reg.nr.: 01-2119486870-28	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;	
	H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;	
	STOT SE 3, H335	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

Where massive quantities of product have been inhaled in aerosol or concentrated vapour forms : remove patient from affected area. transfer to hospital (to an intensive care unit if necessary) by medically equipped ambulance. While awaiting the arrival of medical help, assist the patient's breathing if this is indicated. Clinical and radiographic monitoring will be required over a prolonged period, since delayed pulmonary oedema may occur.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

Revision: 05.06.2019

Printing date 05.06.2019

Version number 3

Trade name: RockCast-150 ISOCYANATE (B)

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Carbon dioxide Fire-extinguishing powder Foam
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN) (Traces)
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- \cdot 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- \cdot 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). After approximately one hour, transfer to suitable drum containers. Do not close these (likelihood of CO2 production). Cover tops only.

Leave open to air in a supervised area for 7 to 14 days before transferring to an authorized dumping site.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Inform personnel of risks associated with the product, the precautions to be taken and procedures to follow where an accident occurs.

Avoid exposure to the material of persons having suffered from chronic respiratory affections (especially asthmatic and bronchitic persons) and those having an isocyanate allergia.

- Information about fire and explosion protection: Protect from heat.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 05.06.2019

Version number 3

Revision: 05.06.2019

(Contd. of page 3)

Trade name: RockCast-150 ISOCYANATE (B)

Protect from humidity and water.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

4,4'-Methylenediphenyl diisocyanate, oligomers

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

· Ingredients with biological limit values:

4,4'-Methylenediphenyl diisocyanate, oligomers

BMGV 1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Fresh air mask Short term filter device:

Filter A/P2

· Protection of hands:



Protective gloves

· Material of gloves

Neoprene gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB

Version number 3

Printing date 05.06.2019

Trade name: RockCast-150 ISOCYANATE (B)

(Contd. of page 4)

· Eye protection:



Safety glasses

Tightly sealed goggles · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and o General Information Appearance: 	chemical properties
Form:	Fluid
Colour:	Yellow
· Odour:	Characteristic
• pH-value at 20 •C:	NA
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	NA e: NA
· Flash point:	> 200 °C (P. Martens)
· Ignition temperature:	>500 °C (DIN 51 794)
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product does not present an explosion hazard.
• Density at 20 •C:	1.21 g/cm ³ (ISO 1675:1985)
 Solubility in / Miscibility with water: organic solvents: 9.2 Other information 	Insoluble. Soluble in many organic solvents. No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Violent reactions with -NHx, -OH and -SH- groups. In the presence of water or humidity gas is produced (CO2) and/or uncontrolled polymerization, possibly leading to internal pressure rises and consequent risk of container breach.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 6)



Version number 3

Revision: 05.06.2019

Printing date 05.06.2019

Trade name: RockCast-150 ISOCYANATE (B)

(Contd. of page 5)

SECTION 11: Toxicological information · 11.1 Information on toxicological effects · Acute toxicity Harmful if inhaled. · LD/LC50 values relevant for classification: 4,4'-Methylenediphenyl diisocyanate, oligomers LD50 >5,000 mg/kg (rat) Oral LD50 >9,400 mg/kg (rabbit)Dermal Inhalative LC50/4 h 0.49 mg/l (rat) · Primary irritant effect: · Skin corrosion/irritation Causes skin irritation. · Serious eye damage/irritation Causes serious eye irritation. · Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Tumors of the lung were observed on animals of laboratory exposed to the MDI in the form of respirable aerosol · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Suspected of causing cancer. • Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

4,4'-Methylenediphenyl diisocyanate, oligomers

LC50 (96h) >1,000 mg / l (fish)

EC50(24h) > 1,000 mg / l (daphnia)

EC50 (72h) >1,640 mg/l (alga)

· 12.2 Persistence and degradability No further relevant information available.

• Other information:

This product is not miscible in water. It acts on water, producing CO2 and polyurea (a solid, non-fusible and insoluble compound) which is, to the best of our knowledge, inert and non-biodegradable. This reaction is promoted by the presence of surfactants such as liquide soap, or water-soluble solvents. Do not dispose of this product or the neutralization products in sewers, rivers or streams.

 \cdot 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

Version number 3

Printing date 05.06.2019



Trade name: RockCast-150 ISOCYANATE (B)

(Contd. of page 6)

• 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB**: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of the product by burning in a suitable incinerator or bury in an approved landfield following all applicable local and/or national regulations.

· European waste catalogue

08 05 01* waste isocyanates

· Uncleaned packaging:

· Recommendation:

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.

Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number		
· ADR, IMDG, IATA	Void	
\cdot 14.2 UN proper shipping name		
· ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	Void	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
 14.5 Environmental hazards: 	Not applicable.	
• 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Annex II of		
Marpol and the IBC Code	Not applicable.	
· Transport/Additional information:	Not dangerous according to the above specifications.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

• Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 56a

(Contd. on page 8)

GB

Revision: 05.06.2019

Printing date 05.06.2019

Version number 3

Trade name: RockCast-150 ISOCYANATE (B)

(Contd. of page 7)

· National regulations:

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 • * Data compared to the previous version altered.